

FLAME RETARDANT MATERIALS

We manufacture a range of resins for use as binders in the production of flame retardant materials, such as furnace lining bricks, blocks, ingot moulds, etc.

Types of resins:

- fine-ground novolak resins,
 liquid phenolic-formaldehyde resins of the resole type,
 phenolic-formaldehyde resins of the novolak type
 novolac liquid phenol-formaldehyde resins



|2

FLAME RETARDANT MATERIALS

SYMBOL	RESIN PROPERTIES						
	FLOW PATH PN-EN ISO 8619 [mm]	HEXAMINE CONTENT OWN METHOD [%]	MELTING POINT PN-EN ISO 3146 [°C]	CURING TIME PN-EN ISO 8987 [s]	FREE PHENOL CONTENT OWN METHOD [%]	WATER CONTENT PN-ISO 760 [%]	SIEVE RESIDUE ANALYSIS OF DRY LASER [%]
MD 4/3	14-20	17,5-18,5			max. 0,5		0,090 mm: max. 5,0
MD 4/4	15-35	8,2-9,2	80-120	100-120	max. 0,9	max. 0,8	0,045 mm: 4-20
MD F-1	16-24		90-110	<u>-</u>	-		0,045 mm: 4-20
MD F-2	30-38	8-10	max. 90	<u>-</u>	-		0,045 mm: 20-30



WE DEVELOP RESINS THAT MEET INDIVIDUAL CUSTOMER REQUIREMENTS

Every year, Lerg markets around 100 new and upgraded products. The quality of its products has been acknowledged by numerous awards and quality certificates, including DNV GL, ISO 9001:2015 Management System Certificate or the Intelligent Development Polish Award and European Quality Certificate.

Lerg has a well-equipped R&D facility and collaborates with international R&D centres, constantly developing innovative solutions for its Customers to cater for their performance-optimised process needs.

Due to the variety of applications of novolak resins as well as specific production profiles of our Customers, technologists from LERG's R&D department lead continuous cooperation with Customers adjusting parameters of resins to their needs, provide professional implementation service, as well as conduct technical and application trainings in the field of resin processing.

| 6



PUSTKÓW - OSIEDLE 59D 39-206 PUSTKÓW 3

tel. + 48 14 680 62 11 fax: + 48 14 680 63 00 lerg@lerg.pl www.lerg.pl

SALES DEPARTMENT

tel. +48 14 680 63 54 tel. + 48 14 680 62 44 handel@lerg.pl

CUSTOMER SERVICE

tel. +48 14 680 62 19 tel. + 48 14 680 65 40 dok@lerg.pl

The above data are based on our current knowledge and research and are believed reliable for possible applications. Due to multiple conditions beyond our control, which can affect processing, the information presented herein does not release the processor from any responsibility in the use of our products and cannot be further deemed any warranty provided by us, nor constitute grounds for any claims of the processor.

